

# BULL8 OM

## AUTOMATIONS FOR SLIDING GATES COMMERCIAL USE

control with built-in encoder and receiver  
personalised release key  
oil lubrication  
**up to 800 kg**



**BULL.P3**

Raised foundation plate included.  
Floor fixing distance 260 x 117, no. 4 Ø 11,  
motor fixing distance 300 x 75 no. 4



### CONTROL PANELS:

BULL8 OM —> CP.BULL8-OM p.128

BULL8 OM.S —> CP.BULL8-OM p.128

## 230 Vac


- Electromechanical 230 Vac geared motor with built-in control unit and encoder
- The encoder device ensures crush prevention and precision in the gate moving phases
- Full metal mechanics and oil lubrication ensure maximum gear durability. The type of oil used is also particularly effective, and ensures maximum efficiency even at low temperatures
- Reduced mechanical wear on components
- Full metal release system
- Version with magnetic limit switches available (BULL8OM.S)



**RI.M4F**  
9272010

M4 rack 30x12x1000mm slotted and galvanized. Supplied with M6 metric screws and threaded spacers.

**Packaging: 4 pcs**



**RI.M4Z**  
9272030

M4 galvanized rack (22x22x2000 mm).

**Packaging: 2 pcs**



**RI.M4P**  
9272020

M4 Nylon rack with steel core, 28x40x1000 mm. Slotted, supplied with self-drilling screws.

**Packaging: 10 pcs**



**SB.BULL8.F**  
9747025

Externally fitted anti-intrusion cable unlock device (L=4.5m).




**ID.TA**  
9846019

Warning board.



**ESA BASIC**  
9176108


System that reduces the electrical energy consumption.



### COMPLETE KITS

#### **KBULL8OM** 9592098

- 1 **BULL8OM** 230 Vac Operator with control unit and built-in receiver
- 1 **PUPILLA.F** Pair of photocells
- 1 **LAMP.LED** 230 Vac Led flashing light with built-in aerial
- 1 **TOKEY** Metal key selector
- 1 **TO.GO2WV** 433.92 MHz Transmitter



### TECHNICAL DATA

	BULL8 OM	BULL8 OM.S
Code	9591523	9591497
Power supply	230 Vac (50-60Hz)	230 Vac (50-60Hz)
Motor supply	230 Vac	230 Vac
Max absorbed current	2.6 A	2.6 A
Max Thrust	940 N	940 N
Opening speed	10.5 m/min	10.5 m/min
Operation cycle	40%	40%
Protection level	IP44	IP44
Magnetic limit switches	<b>NO</b>	<b>YES</b>
Operating temperature	-20°C /+50°C	-20°C /+50°C
Lubrication	<b>OIL</b>	<b>OIL</b>
Max gate weight	800 kg	800 kg
Driving gear for rack	M4 Z18	M4 Z18
Weight	14.2 kg	14.2 kg
<b>Items no. per pallet</b>	<b>36</b>	<b>36</b>
<b>Kits no. per pallet</b>	<b>30</b>	-

**MADE IN ITALY**